

Hydro-Guard® Radio Programming Supplement

Upon the initial set up and programming of your Hydro-Guard Unit(s), the Radio Hand-Held Programmer performs quite similarly to the Plug In Only Programmer. For this reason we recommend that you spend time carefully reviewing the complete Hydro-Guard Programming Guide. The following is a brief supplement designed to outline the additional information the 'Radio Upgrade' end user needs to know when making use of this convenient option.

Initial Set Up:

- 1) Open back of Hand-Held Programmer; install new alkaline battery and close.
- 2) Initialize Hand-Held Programmer as per Programming Guide
- 3) Obtain access to Programming Pod installed within your Hydro-Guard Unit(s) and remove the radio cap(s).
 - Connect Energizer Alkaline battery to Programming Pod's lead.
 - Plug Hand-Held Programmer into Programming Pod
 - Assign the Hand-Held Programmer an Actuator ID (from 1-250) by selecting option #5 from the main menu.
 - Return to main menu and complete programming of Unit as per instructions found in Programming Guide.
 - Unplug Hand-Held Programmer from Programming Pod and reconnect battery and Pod's cap as per schematics.
- 4) Return to Hand-Held Programmer Main Menu and select #3 – Radio Connect.
 - Select Actuator's ID as assigned to current Pod and use ► key to advance through field.
 - Once connected by radio, the Main Menu will read the correct date, time and week (1 or 2) and will also display the assigned Actuator ID #. You may wish to run a brief manual (#2) cycle test (#3) to verify your batteries are fresh and that the radio connection is performing properly.
- 5) The Hydro-Guard Unit is now ready to be placed into service or reprogrammed as required.

Special Notes:

The Pod's internal memory lasts only 3 minutes. Any time the battery within the Programming Pod dies, it is necessary to plug the Hand-Held Programmer directly into the Pod and re-assign the Actuator ID and reprogram the Unit. While repeating the programming steps is only a minor inconvenience, a proactive approach to battery maintenance will serve to alleviate the frequency with which these steps must be completed.

For all other programming questions, please refer to the Hydro-Guard Programming Guide. If the information you require is not available therein, please contact Hydro-Guard® Customer Service at 1.877.277.4520.